

# SUREWET

SUREWET\* additive is the primary wetting agent in the RHELIANT\* system. It also functions as a secondary emulsifier. Additional benefits include improved thermal stability and HTHP filtration control. SUREWET wetting agent is effective over a wide temperature range, in the presence of contaminants, and in reducing the adverse effects of water contamination. SUREWET agent can also be used as a secondary emulsifier in NOVA\* and VERSA\* systems.

## ***Typical Physical Properties***

Physical appearance.....	Light yellow liquid
Specific gravity .....	0.891 @ 68°F (20°C)
Flash point.....	363°F (184°C)
Pour point.....	40 – 60°F (4.4 – 15.6°C)

## ***Applications***

SUREWET additive functions as the wetting agent and secondary emulsifier in the RHELIANT system, when used in combination with the SUREMUL\* primary emulsifier. It can also be used as a secondary emulsifier in NOVA systems and in the VERSA family of systems in conjunction with a primary emulsifier.

SUREWET additive preferentially wets barite and drill solids to prevent water-wetting of solids. Secondary functions include: improves thermal stability, rheological stability, filtration control and emulsion stability as well as improves a system's resistance to contamination.

Initial formulation concentrations range from 1 to 3 lb/bbl (2.85 to 8.6 kg/m<sup>3</sup>) with occasional daily treatments of 0.063 lb/bbl (0.18 kg/m<sup>3</sup>), depending on the synthetic-water ratio, anticipated temperatures, desired properties and other products used in the formulation.

---

### ***Advantages***

- Aids in providing improved wetting of solids in the system
- Tightens the emulsion and increases the thermal stability
- Lowers fluid loss
- Reduces risk of water in filtrate

### ***Limitations***

- Avoid storage conditions where temperatures are less than 60°F (16°C).

### ***Toxicity and Handling***

Bioassay information is available upon request.

Handle as an industrial chemical, wearing protective equipment and observing the precautions as described in the Material Safety Data Sheet (MSDS).

### ***Packaging and Storage***

SUREWET additive is packaged in 55-gal (208-L), steel drums and 550-gal (2131-L) totes.

Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatible materials.



P.O. Box 42842  
Houston, Texas 77242-2842  
Tel: 281-561-1300  
Fax: 281-561-1441  
[www.miswaco.com](http://www.miswaco.com)  
E-mail: [questions@miswaco.com](mailto:questions@miswaco.com)

This document is supplied solely for informational purposes and M-I SWACO makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.